

# **TT 25-SMA**

# ACTIVE PRECISION STAGE MONITOR

#### **DESCRIPTION**

The TT25-SMA is a full range, high performance coaxial stage monitor. The linear curve response, the consistent coverage and acoustic output make the TT25-SMA the professional choice for most demanding situations. The voicing is accurate and deep, the sound transparent in the mids and extremely accurate at very high frequencies. The size is compact and the profile very low for a discrete stage professional appearance. Loop through output and power panel on opposite side to minimize cable runs on stage.



#### **FEATURES**

- 750 W switching amplifiers
- 60° conical, constant directivity coverage angle
- 3.5" voice coil, neodymium woofer
- 2.5" voice coil, neodymium compression driver
- · High quality analog input board
- Soft limiter RMS protection
- Verv low profile
- Very high output



## **TECHNICAL SPECIFICATIONS**

Acoustical specifications	Frequency Response:	50 Hz ÷ 20000 Hz
•	Max SPL @ 1m:	131 dB
	Horizontal coverage angle:	60°
	Vertical coverage angle:	60°
Transducers	Compression Driver:	1.5" neo, 2.5" v.c
	Woofer:	15" neo, 3.5" v.c
Input/Output section	Input signal:	bal/unbal
	Input connectors:	XLR
	Output connectors:	XLR
	Input sensitivity:	-2 dBu/+4 dBu
Processor section	Crossover Frequencies:	1200 Hz
	Protections:	Thermal, HF
	Limiter:	Fast Limiter
	Controls:	Side/floor coupling
Power section	Total Power:	1500 W Peak, 750 W RMS
	High frequencies:	500 W Peak, 250 W RMS
	Low frequencies:	1000 W Peak, 500 W RMS
	Cooling:	Convection
	Connections:	Powercon IN/OUT
Standard compliance	CE marking:	Yes
Physical specifications	Cabinet/Case Material:	Baltic birch plywood
	Handles:	2 on side
	Grille:	Steel
	Color:	Black
Size	Height:	330 mm / 12.99 inches
	Width:	580 mm / 22.83 inches
	Depth:	432 mm / 17.01 inches
	Weight:	20 kg / 44.09 lbs
Shipping informations	Package Height:	670 mm / 26.38 inches
	Package Width:	510 mm / 20.08 inches
	Package Depth:	420 mm / 16.54 inches
	Package Weight:	22.5 kg / 49.6 lbs



## **PART NUMBER**

• 13000121

TT 25-SMA

• **13000118**TT 25-SMA

115V

220-240V

EAN 8024530008222

EAN 8024530008192